	SAFETY DATA SHEET	Page : 1 / 14
		Revision nr : 3.0
	Gasoline	Issue date : 20/03/2018
		Supersedes : 16/08/2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance
Trade name/designation : Gasoline
Chemical name : Gasoline
EC Index : 649-378-00-4
EC-No. : 289-220-8
CAS-No. : 86290-81-5
REACH registration No : 01-2119471335-39-0145
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Fuels
Further information: see exposure scenarios attached to this safety data sheet.

Title	Use descriptors
Distribution (ES Ref.: 03b (Benz 0%-1%))	PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC15, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7, ESVOC SPERC 1.1b.v1
Use as a fuel (ES Ref.: 10b (Benz 0%-1%))	PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16, ERC7, ESVOC SPERC 7.12a.v1
Use as a fuel (ES Ref.: 11b (Benz 0%-1%))	PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16, ERC9a, ERC9b, ESVOC SPERC 9.12b.v1
Use as a fuel (ES Ref.: 12b (Benz 0%-1%))	PC13, ERC9a, ERC9b, ESVOC SPERC 9.12c.v1
Formulation & (re)packing of substances and mixtures (ES Ref.: 04b (Benz 0%-1%))	PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC15, ERC2, ESVOC SPERC 2.2.v1

Full text of use descriptors: see section 16

1.2.2. Uses advised against

No data available


1.3. Details of the supplier of the safety data sheet

Trafigura Ventures V.B.V.
Evert van de Beekstraat 1-82
The Base, Tower B - 5th Floor
1118 CL Schiphol - The Netherlands
T +31 20 504 1800
TrafiguraReach@trafigura.com

1.4. Emergency telephone number

Emergency number : +32 3 575 03 30
This telephone number is available 24 hours per day, 7 days per week.

Country	Official advisory body	Address	Emergency number
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	+353 1 809 21 66 (public, 8am - 10pm, 7/7) +353 01 809 2566 (Professionals, 24/7)

	SAFETY DATA SHEET	Page : 2 / 14
		Revision nr : 3.0
	Gasoline	Issue date : 20/03/2018
		Supersedes : 16/08/2016

Country	Official advisory body	Address	Emergency number
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre, Wolfson Unit	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0844 892 0111 (UK only, 24/7, healthcare professionals only)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 1	H224
Skin Irrit. 2	H315
Muta. 1B	H340
Carc. 1B	H350
Repr. 2	H361
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Chronic 2	H411

Full text of H statements : see section 16

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word :

Danger

Hazard statements (CLP) :

: H224 - Extremely flammable liquid and vapour.
 H304 - May be fatal if swallowed and enters airways.
 H315 - Causes skin irritation.
 H336 - May cause drowsiness or dizziness.
 H340 - May cause genetic defects.
 H350 - May cause cancer.
 H361 - Suspected of damaging fertility or the unborn child.
 H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) :


: P201 - Obtain special instructions before use.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 - Keep container tightly closed.
 P301+P310+P331 - IF SWALLOWED: Immediately call a POISON CENTER, a doctor. Do NOT induce vomiting.
 P308+P313 - IF exposed or concerned: Get medical advice.
 P403+P235 - Store in a well-ventilated place. Keep cool.

Extra phrases :

: EUH210 - Safety data sheet available on request.

Listed in Annex VI :

: EC Index-No. : 649-378-00-4

	SAFETY DATA SHEET	Page : 3 / 14
		Revision nr : 3.0
	Gasoline	Issue date : 20/03/2018
		Supersedes : 16/08/2016

2.3. Other hazards

Other hazards : PBT/vPvB data. This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.1. Substances

Comments : UVCB
Substance name : Gasoline
CAS-No. : 86290-81-5
EC-No. : 289-220-8
EC Index : 649-378-00-4

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Gasoline	(CAS-No.) 86290-81-5 (EC-No.) 289-220-8 (EC Index) 649-378-00-4 (REACH-no) 01-2119471335-39	100	Flam. Liq. 1, H224 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Muta. 1B, H340 Carc. 1B, H350 STOT SE 3, H336 Aquatic Chronic 2, H411 Repr. 2, H361fd

Full text of H-statements: see section 16

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

Additional advice : First aider: Pay attention to self-protection. See also section 8 . Never give anything by mouth to an unconscious person. Show this safety data sheet to the doctor in attendance. In case of doubt or persistent symptoms, consult always a physician. Treat symptomatically.

Inhalation : Keep at rest. Provide fresh air. Give oxygen or artificial respiration if necessary. Call a physician immediately.

Skin contact : Take off immediately all contaminated clothing. Wash with plenty of water/. Wash contaminated clothing before reuse. In case of doubt or persistent symptoms, consult always a physician.

Eyes contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists: Get medical advice/attention.


Ingestion : Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation : Vapours may cause drowsiness and dizziness. The following symptoms may occur: Mental confusion. Cough. Headache . Irritating to respiratory system.

Skin contact : The following symptoms may occur: Irritating to skin. erythema (redness). Repeated exposure may cause skin dryness or cracking.

Eyes contact : Contact with eyes may cause irritation.

	SAFETY DATA SHEET	Page : 4 / 14
		Revision nr : 3.0
	Gasoline	Issue date : 20/03/2018
		Supersedes : 16/08/2016

Ingestion : Harmful: may cause lung damage if swallowed. Risk of pneumonia. The following symptoms may occur: Nausea, Vomiting, Diarrhoea.

Chronic symptoms : May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child.

4.3. Indication of any immediate medical attention and special treatment needed

If swallowed, do not induce vomiting - seek medical advice.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray, Alcohol resistant foam, Carbon dioxide, Dry extinguishing powder.

Unsuitable extinguishing media : Strong water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Heating causes rise in pressure with risk of bursting. Vapours may form explosive mixture with air. Vapours are heavier than air and may spread along floors. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. Hazardous decomposition products COx. Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Evacuate personnel to a safe area. Special protective equipment for firefighters. . In case of fire: Wear self-contained breathing apparatus. Use water spray or fog for cooling exposed containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

For non-emergency personnel : Evacuate personnel to a safe area. Stay upwind/keep distance from source. Provide adequate ventilation. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Avoid contact with skin and eyes. Do not breathe vapour/aerosol. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ensure equipment is adequately earthed. Use explosion-proof equipment. Use only non-sparking tools.

6.1.2. For emergency responders

For emergency responders : Ensure procedures and training for emergency decontamination and disposal are in place. Concerning personal protective equipment to use, see section 8 .

6.2. Environmental precautions


Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Stop leak if safe to do so. Dam up. Take up liquid spill into absorbent material, e.g.: sand, earth, vermiculite or powdered limestone. Collect in closed and suitable containers for disposal. Recover large spills by pumping (use an explosion proof or hand pump). Dispose of as special waste in compliance with local and national regulations. Site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

	SAFETY DATA SHEET	Page : 5 / 14
		Revision nr : 3.0
	Gasoline	Issue date : 20/03/2018
		Supersedes : 16/08/2016

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: May release poisonous hydrogen sulfide.
Precautions for safe handling	: Provide adequate information, instruction and training for operators. Provide adequate ventilation. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Avoid contact with skin, eyes and clothing. Do not breathe vapour/aerosol. Take precautionary measures against static discharges. Ensure equipment is adequately earthed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take any precaution to avoid mixing with combustibles... See also section 10. Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time). Do not allow to enter into surface water or drains. Product may release Hydrogen Sulphide: A specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances.
Hygiene measures	: Keep good industrial hygiene. Take off contaminated clothing. Wash hands and face before breaks and immediately after handling of the product. When using do not eat, drink or smoke. Separate working clothes from town clothes. Keep away from food, drink and animal feedingstuffs.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Storage of flammable liquids. Keep container tightly closed in a cool, well-ventilated place. Do not store near or with any of the incompatible materials listed in section 10.
Incompatible substances or mixtures	: Oxidizing agent.
Storage temperature	: Ambient temperature
Heat and ignition sources	: Keep away from open flames, hot surfaces and sources of ignition. Do not smoke.
Special rules on packaging	: Keep in properly labelled containers.
Packaging materials	: Keep only in the original container. Suitable material: Stainless steel, Mild steel.


7.3. Specific end use(s)

see attached exposure scenario.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Gasoline (86290-81-5)		
Belgium	Limit value (mg/m ³)	903 mg/m ³
Belgium	Limit value (ppm)	300 ppm
Belgium	Short time value (mg/m ³)	1501 mg/m ³
Belgium	Short time value	500 ppm
Czech Republic	Expoziční limity (PEL) (mg/m ³)	400 mg/m ³
Lithuania	IPRV (mg/m ³)	200 mg/m ³
Lithuania	TPRV (mg/m ³)	300 mg/m ³
Netherlands	Grenswaarde TGG 8H (mg/m ³)	240 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	480 mg/m ³
Portugal	OEL TWA (ppm)	300 ppm
Portugal	OEL STEL (ppm)	500 ppm
Spain	VLA-ED (ppm)	300 ppm (manufacturing, commercialization and use restrictions according to REACH)
Sweden	nivågränsvärde (NVG) (mg/m ³)	250 mg/m ³

	SAFETY DATA SHEET	Page : 6 / 14
		Revision nr : 3.0
	Gasoline	Issue date : 20/03/2018
		Supersedes : 16/08/2016

Gasoline (86290-81-5)		
Switzerland	MAK (mg/m ³)	1100 mg/m ³
Switzerland	MAK (ppm)	300 ppm
Australia	TWA (mg/m ³)	900 mg/m ³
USA - ACGIH	ACGIH TWA (ppm)	300 ppm
USA - ACGIH	ACGIH STEL (ppm)	500 ppm

Gasoline (86290-81-5)		
DNEL/DMEL (workers)		
Acute - systemic effects, inhalation	(15min)	1300 mg/m ³
Acute - local effects, inhalation	(15min)	1100 mg/m ³
Long-term - local effects, inhalation	(8h)	840 mg/m ³
DNEL/DMEL (general population)		
Acute - systemic effects, inhalation	(15min)	1200 mg/m ³
Acute - local effects, inhalation	(15min)	640 mg/m ³
Long-term - local effects, inhalation	(24h)	180 mg/m ³
PNEC (additional information)		
Additional information	Substance of unknown or variable composition, complex reaction products or biological material (UVCB). No data available	


8.2. Exposure controls

Engineering measure(s)	: Provide adequate ventilation. Use only in area provided with appropriate exhaust ventilation. Closed system. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Take precautionary measures against static discharge. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Organisational measures to prevent /limit releases, dispersion and exposure. See also section 7.
Personal protective equipment	: The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Hand protection	: The selection of specific gloves for a specific application and time of use in a working area, should also take into account other factors on the working space, such as (but not limited to): other chemicals that are possibly used, physical requirements (protection against cutting/drilling, skill, thermal protection), and the instructions/specification of the supplier of gloves. - rubber gloves. (EN 374): NBR (Nitrile rubber). Material thickness: >0,54mm. Breakthrough time : >360min. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove.
Eye protection	: Safety glasses with side shields
Body protection	: Wear suitable coveralls to prevent exposure to the skin. Use chemically protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Filter type: A (EN 141). Half-face mask (DIN EN 140). full face mask (DIN EN 136). Self-contained open-circuit compressed air breathing apparatus (EN 137)
Thermal hazard protection	: Not required for normal conditions of use. Use dedicated equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: liquid.

	SAFETY DATA SHEET	Page : 7 / 14
		Revision nr : 3.0
	Gasoline	Issue date : 20/03/2018
		Supersedes : 16/08/2016

Colour	: Yellow.
Odour	: petroleum hydrocarbon odour.
Odour threshold	: Not determined No data available
pH	: Not determined
Relative evaporation rate (butylacetate=1)	: No data available
Melting / freezing point	: < -60 °C
Freezing point	: No data available
Initial boiling point and boiling range	: < 35 °C
Flash point	: < 0 °C
Auto-ignition temperature	: > 220 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable, liquid
Vapour pressure	: 200 mmHg @ 20°C
Vapour density	: > 2
Relative density	: 0,62 - 0,88 g/cm ³ @ 15°C
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water	: 1 - 8
Kinematic viscosity	: 1 mm ² /s @ 20°C
Dynamic viscosity	: No data available
Explosive properties	: Vapours may form explosive mixture with air. Not explosive.
Oxidising properties	: Not applicable. The classification procedure needs not to be applied because there are no chemical groups present in the molecule which are associated with oxidising properties.
Explosive limits	: 1 - 10 vol %

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable. Reacts with oxidants. Reference to other sections: 10.5.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air. May release : H₂S. See also section 7. Handling and storage.

10.4. Conditions to avoid


Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Direct sunlight. See also section 7. Handling and storage.

10.5. Incompatible materials

oxidising substances. Strong acids and strong bases. See also section 7. Handling and storage.

10.6. Hazardous decomposition products

Highly toxic fumes. Hydrogen sulfide (H₂S). SO_x. Carbon oxides (CO, CO₂).

	SAFETY DATA SHEET	Page : 8 / 14
		Revision nr : 3.0
	Gasoline	Issue date : 20/03/2018
		Supersedes : 16/08/2016

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified (Based on available data, the classification criteria are not met.)

Gasoline (86290-81-5)	
LD50/oral/rat	> 5000 mg/kg
LD50/dermal/rat	> 2000 mg/kg
LC50/inhalation/4h/rat	> 5610 mg/m ³

Gasoline (86290-81-5)	
LD50/oral/rat	> 5000 mg/kg
LD50/dermal/rat	> 2000 mg/kg
LC50/inhalation/4h/rat	> 5610 mg/m ³

Skin corrosion/irritation : Causes skin irritation.
pH: Not determined

Serious eye damage/irritation : Not classified (Based on available data, the classification criteria are not met.)
pH: Not determined

Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met.)

Germ cell mutagenicity : May cause genetic defects.

Carcinogenicity : May cause cancer.

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

STOT-single exposure : May cause drowsiness or dizziness.

Gasoline (86290-81-5)	
LOAEL, male, acute, Inhalation, Rat, systemic	4320 mg/m ³ (1 hours)

Gasoline (86290-81-5)	
LOAEL, male, acute, Inhalation, Rat, systemic	4320 mg/m ³ (1 hours)

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met.)

Aspiration hazard : May be fatal if swallowed and enters airways.

Gasoline (86290-81-5)	
Kinematic viscosity	1 mm ² /s @ 20°C


Other information : Symptoms related to the physical, chemical and toxicological characteristics.
Reference to other sections: 4.2.

SECTION 12: Ecological information

12.1. Toxicity

Environmental properties : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Gasoline (86290-81-5)	
LL50, fish, acute, Freshwater, Pimephales promelas (fathead minnow)	8.2 mg/l (96 hours, equivalent or similar to EPA 66013-75-009)
NOELR, fish, Chronic, Freshwater, Pimephales promelas (fathead minnow)	2.6 mg/l (14 days, OECD 204)
EL50, daphnia, acute, Freshwater, daphnia	4.5 mg/l (48 hours, OECD Test Guideline 202)
NOELR, daphnia, Chronic, Freshwater, daphnia	2.6 mg/l (21 days, OECD 211)

	SAFETY DATA SHEET	Page : 9 / 14
		Revision nr : 3.0
	Gasoline	Issue date : 20/03/2018
		Supersedes : 16/08/2016

Gasoline (86290-81-5)	
EL50, algae, Freshwater, Pseudokirchneriella subcapitata	3.1 mg/l (72 hours, OECD Test Guideline 201)
LL50, microorganisms, Freshwater, Tetrahymena pyriformis	15.41 mg/l (72 hours, Quantitative structure-activity relationship (QSAR))

Gasoline (86290-81-5)	
LL50, fish, acute, Freshwater, Pimephales promelas (fathead minnow)	8.2 mg/l (96 hours, equivalent or similar to EPA 66013-75-009)
NOELR, fish, Chronic, Freshwater, Pimephales promelas (fathead minnow)	2.6 mg/l (14 days, OECD 204)
EL50, daphnia, acute, Freshwater, daphnia	4.5 mg/l (48 hours, OECD Test Guideline 202)
NOELR, daphnia, Chronic, Freshwater, daphnia	2.6 mg/l (21 days, OECD 211)
EL50, algae, Freshwater, Pseudokirchneriella subcapitata	3.1 mg/l (72 hours, OECD Test Guideline 201)
LL50, microorganisms, Freshwater, Tetrahymena pyriformis	15.41 mg/l (72 hours, Quantitative structure-activity relationship (QSAR))

12.2. Persistence and degradability

Gasoline (86290-81-5)	
Persistence and degradability	Readily biodegradable.

12.3. Bioaccumulative potential

Gasoline (86290-81-5)	
Partition coefficient n-octanol/water	1 - 8

Gasoline (86290-81-5)	
Partition coefficient n-octanol/water	NA: UVCB

12.4. Mobility in soil

Gasoline (86290-81-5)	
Ecology - soil	Low mobility (soil).

12.5. Results of PBT and vPvB assessment

No data available


12.6. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods






Product/Packaging disposal recommendations	: Handle with care. Safe handling: see section 7. Handling and storage. Dispose of contaminated materials in accordance with current regulations. Refer to manufacturer/supplier for information on recovery/recycling. Collect and dispose of waste product at an authorised disposal facility.
Additional information	: Do not puncture or incinerate. Do not burn, or use a cutting torch on the empty drum. Delivery to an approved waste disposal company.
Further ecological information	: Do not allow to enter into surface water or drains.

	SAFETY DATA SHEET	Page : 10 / 14
		Revision nr : 3.0
	Gasoline	Issue date : 20/03/2018
		Supersedes : 16/08/2016

European waste catalogue (2001/573/EC, 75/442/EEC, 91/689/EEC) : Classified as hazardous waste according to European Union regulations. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
The following Waste Codes are only suggestions:
130702 - petrol
150110 - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information


In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
1268	1268	1268	1268	1268
14.2. UN proper shipping name				
GAS OIL / DIESEL FUEL / HEATING OIL, LIGHT	PETROLEUM DISTILLATES, N.O.S.	Petroleum distillates, n.o.s.	PETROLEUM DISTILLATES, N.O.S.	PETROLEUM DISTILLATES, N.O.S.
Transport document description				
UN 1268 GAS OIL / DIESEL FUEL / HEATING OIL, LIGHT, 3, I, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, I, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1268 Petroleum distillates, n.o.s., 3, I, ENVIRONMENTALLY HAZARDOUS	UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, I, ENVIRONMENTALLY HAZARDOUS	UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, I, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
I	I	I	I	I
14.5. Environmental hazards				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
ADN :N2				

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : F1
Special provisions : 363, 664
Limited quantities (ADR) : 500ml
Excepted quantities (ADR) : E2
Packing instructions (ADR) : P001
Mixed packing provisions (ADR) : MP7, MP17
Portable tank and bulk container instructions (ADR) : T11
Portable tank and bulk container special provisions (ADR) : TP1, TP8

	SAFETY DATA SHEET	Page : 11 / 14
		Revision nr : 3.0
	Gasoline	Issue date : 20/03/2018
		Supersedes : 16/08/2016

Tank code (ADR) : L4BN
 Vehicle for tank carriage : FL
 Transport category (ADR) : 1
 Special provisions for carriage - Operation (ADR) : S2, S20
 Hazard identification number (Kemler No.) : 33
 Orange plates :



Tunnel restriction code : D/E
 EAC code : 3YE

- Transport by sea

Special provisions (IMDG) : 363
 Limited quantities (IMDG) : 500 ml
 Excepted quantities (IMDG) : E3
 Packing instructions (IMDG) : P001
 Tank instructions (IMDG) : T11
 Tank special provisions (IMDG) : TP1, TP8
 EmS-No. (Fire) : F-E
 EmS-No. (Spillage) : S-E
 Stowage category (IMDG) : E
 Properties and observations (IMDG) : Immiscible with water.

- Air transport


PCA Excepted quantities (IATA) : E3
 PCA Limited quantities (IATA) : Forbidden
 PCA limited quantity max net quantity (IATA) : Forbidden
 PCA packing instructions (IATA) : 351
 PCA max net quantity (IATA) : 1L
 CAO packing instructions (IATA) : 361
 CAO max net quantity (IATA) : 30L
 Special provisions (IATA) : A3
 ERG code (IATA) : 3H

- Inland waterway transport

Classification code (ADN) : F1
 Special provisions (ADN) : 363
 Limited quantities (ADN) : 500 ml
 Excepted quantities (ADN) : E3
 Carriage permitted (ADN) : T
 Equipment required (ADN) : PP, EX, A
 Ventilation (ADN) : VE01
 Number of blue cones/lights (ADN) : 1

- Rail transport

Classification code (RID) : F1

	SAFETY DATA SHEET	Page : 12 / 14
	Gasoline	Revision nr : 3.0
		Issue date : 20/03/2018
		Supersedes : 16/08/2016

Special provisions (RID)	: 363
Limited quantities (RID)	: 500ml
Excepted quantities (RID)	: E3
Packing instructions (RID)	: P001
Mixed packing provisions (RID)	: MP7, MP17
Portable tank and bulk container instructions (RID)	: T11
Portable tank and bulk container special provisions (RID)	: TP1, TP8
Tank codes for RID tanks (RID)	: L4BN
Transport category (RID)	: 1
Hazard identification number (RID)	: 33

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Code: IBC : This product is being carried under the scope of MARPOL Annex I Gasolines.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations


The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	Gasoline - Gasoline
3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	Gasoline - Gasoline
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Gasoline - Gasoline
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	Gasoline - Gasoline
28. Substances which appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 classified as Carcinogen category 1A or 1B (Table 3.1) or Carcinogen category 1 or 2 (Table 3.2) and listed as follows: Carcinogen category 1A (Table 3.1)/Carcinogen category 1 (Table 3.2) listed in Appendix 1 Carcinogen category 1B (Table 3.1)/Carcinogen category 2 (Table 3.2) listed in Appendix 2	Gasoline - Gasoline
29. Substances which appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 classified as Germ cell Mutagen category 1A or 1B (Table 3.1) or Mutagen category 1 or 2 (Table 3.2) and listed as follows: Mutagen category 1A (Table 3.1)/Mutagen category 1 (Table 3.2) listed in Appendix 3 Mutagen category 1B (Table 3.1)/Mutagen category 2 (Table 3.2) listed in Appendix 4	Gasoline - Gasoline
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	Gasoline - Gasoline

Gasoline is not on the REACH Candidate List

Gasoline is not on the REACH Annex XIV List

15.1.2. National regulations

	SAFETY DATA SHEET	Page : 13 / 14
		Revision nr : 3.0
	Gasoline	Issue date : 20/03/2018
		Supersedes : 16/08/2016

Germany

Reference to AwSV : Water hazard class (WGK) 3, severe hazard to waters (Classification according to VwVwS, Annex 1 or 2; ID No. 204)

Risk classification according to VbF : A I - Liquids with a flashpoint below 21°C

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

TA Luft : Mutagenetic

Netherlands

Waterbezwaarlijkheid : 6 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SZW-lijst van kankerverwekkende stoffen : Gasoline is listed

SZW-lijst van mutagene stoffen : Gasoline is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : The substance is not listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : The substance is not listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : The substance is not listed

Denmark

Class for fire hazard : Class I-1

Store unit : 1 liter

Recommendations Danish Regulation :

15.2. Chemical safety assessment

For this substance a chemical safety assessment has been carried out


SECTION 16: Other information

Indication of changes:

SECTION 1,2,3,7,9,10,14,15,16.

Abbreviations and acronyms:

ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin
ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC
IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods Code
LEL = Lower Explosive Limit/Lower Explosion Limit
UEL = Upper Explosion Limit/Upper Explosive Limit
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
N = Dangerous for the environment
TWA = time weighted average
vPvB = very persistent and very bioaccumulating
WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act)
T = Toxic
TLV = Threshold limits
STEL = Short term exposure limit
DNEL = Derived No Effect Level

	SAFETY DATA SHEET	Page : 14 / 14
		Revision nr : 3.0
	Gasoline	Issue date : 20/03/2018
		Supersedes : 16/08/2016

	CSR = Chemical Safety Report
	EC50 = Median Effective Concentration
	UVCB = Substance of unknown or variable composition, complex reaction products or biological material (UVCB)

Sources of key data used to compile the datasheet : European Chemicals Bureau CSR Low Boiling Point Naphthas Concawe.

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment - chronic hazard category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Flam. Liq. 1	Flammable liquids, Category 1
Muta. 1B	Germ cell mutagenicity, hazard categories 1B
Repr. 2	Reproductive toxicity, Hazard Category 2
Repr. 2	Reproductive toxicity, Hazard Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H224	Extremely flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.
EUH210	Safety data sheet available on request.

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Classification according to Regulation (EC) No. 1272/2008 [CLP]
Labelling according to Regulation (EC) No. 1272/2008 [CLP]

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.